## **HellermannTyton**



Article Number: 170-03123

Description: Braided Sleeving, Expandable, Fray Resistant, .125" Dia,

PET, Black, 100 ft/reel

Base Data		
	Local Order Number	170-03123
	Туре	BSPSC180
	Color	Black (BK)
	Features and Benefits	<ul> <li>Cuts with scissors without fraying ends enables field installations without need for hot knife.</li> <li>Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.</li> <li>Expands to 150% of easy installation and reduced assembly time requirements.</li> </ul>
	Quantity Per	reel
	Product Description	A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors.
	Short Description	Braided Sleeving, Expandable, Fray Resistant, .125" Dia, PET, Black, 100 ft/reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.48m
	Reel Length (imperial)	100.0ft
	Bundle Diameter Min. (Imperial)	0.125"
	Bundle Diameter Min. (Metric)	3.2mm
	Bundle Diameter Max. (Imperial)	0.25"
	Bundle Diameter Max. (Metric)	6.4mm
	Nominal Diameter (Imperial)	1/8"
	Nominal Diameter (Metric)	3.3mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	UL 94 V0

generated on: 4/28/2017

## 170-03123



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.4lbs
	Weight (Metric)	0.18kg

generated on: 4/28/2017