

Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234 E-mail: saleshelp@tripplite.com

# Model #: DG115-SR

### Waber-by-Tripp Lite Surge Suppressor with heavy-duty metal housing



#### **Highlights**

- 6 outlets/6 ft. cord
- 600 joule rating
- Audible surge indication
- Remote switch included

#### **Description**

The Waber-by-Tripp Lite DG115-SR Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Unique design includes remote power switch at the end of a 6 foot cord allows remote power control of connected equipment. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 600 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip with remote power switch on a 6 ft. cord

SUPPRESSION - 600 joules AC suppression

Applications

 Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

#### Package Includes

- DG115-SR Power Strip
- Warranty information
- Instruction manual

#### **Features**

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Mountable remote power switch at the end of a 6 foot cord allows remote power control of connected equipment.
- Includes 6 NEMA 5-15R output receptacles
- · Lighted combination power switch with integrated circuit breaker
- . Keyhole mounting tabs support permanent installation on a wide variety of surfaces

- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty

## Specifications

OVERVIEW		
Intended Application	Industrial/Factory Floor	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Circuit Breaker (amps)	15	
Outlet quantity / type	6 NEMA 5-15R	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P input plug	
Input cord length (ft.)	6	
Input cord length (m)	1.8	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Lighted two position mountable remote power switch at the end of a dedicated 6 ft. cord controls power to all outlets	
Diagnostic LEDs	Protection present (green)	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	600	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 let through rating	400V - UL Verified	
EMI / RFI filtering	Up to 20dB	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESS	DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (HWD/in)	12.5 x 2.5 x 1.5	

Unit Dimensions (HWD/cm)	31.75 x 6.35 x 3.8	
Material of construction	Metal	
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting	
Receptacle Color	Gray	
AC line cord color	Gray	
Style	Strip	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=1968.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.