

Article Number: 596-00202

Description: Foam Nameplate, 2.38" x 2.38" Emergency Stop label, PET, Yellow, 100/roll



Base Data	
Local Order Number	596-00202
Type	NPL60X60YE
Color	Yellow (YE)
Features and benefits	<ul style="list-style-type: none"> <li>• Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.</li> <li>• Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.</li> <li>• Labels are UV and chemical resistant for long life in an industrial environment.</li> <li>• Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.</li> </ul>
Quantity Per	reel
Product Description	The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Institute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.
Technical Description	Foam Nameplate, 2.375" X 2.375" Emergency Stop label, PET, Yellow
Short Description	Foam Nameplate, 2.38" x 2.38" Emergency Stop label, PET, Yellow, 100/roll
Product Dimensions	
Length L (Imperial)	2.375"
Length L (Metric)	60.3mm
Self adhesive (Yes/No)	Yes
Width W (Imperial)	2.375"
Width W (Metric)	60.3mm
Height H (Imperial)	2.375"
Height H (Metric)	60.3mm
Mounting Hole Diameter D (Imperial)	1.20"
Mounting Hole Diameter D (Metric)	30.48 mm
Horizontal Repeat HR (metric)	66.6mm
Horizontal Repeat HR (imperial)	2.625"

596-00202

# HellermannTyton

Product Dimensions	Print Method	Thermal transfer
	Vertical Repeat VR (imperial)	2.375"
	Vertical Repeat VR (metric)	60mm
	Width of Liner WL (metric)	64.77mm
	Width of Liner WL (imperial)	2.55"
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +176°F (-40°C to +80°C)
	Operating Temperature	-40°F to +176°F (-40°C to +80°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3919102055