

181-15500



Article Number: 181-15500

Description: Solid Cable and Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, Black, 120 ft/carton

Base Data	
Local Order Number	181-15500
Type	SD1.5X1.5
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li> <li>• Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul>
Quantity Per	carton
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Technical Description	Non-Adhesive
Short Description	Solid Cable and Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, Black, 120 ft/carton
Product Dimensions	
Length L (Imperial)	6.0ft
Length L (Metric)	1.83m
Width W (Imperial)	1.5"
Width W (Metric)	38.1mm
Width W2 (Imperial)	1.5"
Width W2 (Metric)	38.1mm
Height H (Imperial)	1.57"
Height H (Metric)	39.9mm
Mounting Hole Centers (Imperial)	4.0"

181-15500



Material and Specifications		
	Material	Polyvinylchloride (PVC)
	Material Shortcut	PVC
	Flammability	self-extinguishing
	Operating Temperature	+122°F (+50°C)
	ROHS Compliant	Yes
	Certification/Specification	CSA
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	120ft
	Package Quantity (Metric)	36.6m
	Customs Number(Schedule B)	3925900000