

Article Number: 594-57788

Description: Laser Tag Label, 2.75" x 4.25", 8 Per Sheet, PET, White,

2000/pkg

HellermannTyton

| Base Data | | |
|-----------------------|-------------------------------------|---|
| | Local Order Number | TAG57L-788 |
| | Туре | TAG57L |
| | Color | White (WH) |
| | Features and benefits | LaserTags are sheet fed for easy loading and fast printing. LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing. LaserTags are printable using toner for long term UV exposure. LaserTags come in a variety of label sizes and types to fit most applications. |
| | Quantity Per | pack |
| | Product Description | LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers. |
| | Short Description | Laser Tag Label, 2.75" x 4.25", 8 Per Sheet, PET, White, 2000/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 2.75" |
| | Length L (Metric) | 69.8mm |
| | Width W (Imperial) | 4.25" |
| | Width W (Metric) | 107.9mm |
| | Height H (Imperial) | 2.75" |
| | Height H (Metric) | 69.8mm |
| | Height of printable area (imperial) | 2.75" |
| | Height of printable area (metric) | 69.8mm |
| | Horizontal Repeat HR (imperial) | 4.250" |
| | Horizontal Repeat HR (metric) | 107.90mm |
| | Print Method | Laser |
| | Thickness T (Metric) | 64.0µm |
| | Vertical Repeat VR (metric) | 69.80mm |

generated on: 4/29/2017

594-57788



| Product Dimensions | Vertical Repeat VR (imperial) | 2.75" |
|--------------------------------|---------------------------------|--|
| Material and Specifications | | |
| | Material | Type 788, Polyetylenterephthalat (PET) |
| | Material Shortcut | 788 |
| | Adhesive | Acrylic |
| | Adhesive Operating Temperature | -40°F to +199°F (-40°C to +93°C) |
| | Minimum Application Temperature | from +50°F (from +10°C) |
| | Operating Temperature | -40°F to +199°F (-40°C to +93°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 2000 |
| | Package Quantity (Metric) | 2000 |
| | Customs Number(Schedule B) | 3919905060 |
| | Labels per Column | 4 |
| | Labels per Row | 2 |
| | Labels per Sheet | 8 |

generated on: 4/29/2017