

181-33000



Article Number: 181-33000

Description: Solid Cable and Wiring Duct, 3" x 3", Non-Adhesive, PVC, Black, 120 ft/carton

|                                  |                       |  |
|----------------------------------|-----------------------|--|
| Base Data                        | Local Order Number    | 181-33000  |
|                                  | Type                  | SD3X3  |
|                                  | Color                 | Black (BK)   |
|                                  | Features and Benefits | <ul style="list-style-type: none"> <li>• A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li> <li>• Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul> |
|                                  | Quantity Per          | carton   |
|                                  | Product Description   | HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.   |
|                                  | Technical Description | Non-Adhesive   |
|                                  | Short Description     | Solid Cable and Wiring Duct, 3" x 3", Non-Adhesive, PVC, Black, 120 ft/carton  |
|                                  | Product Dimensions    | Length L (Imperial)  |
| Length L (Metric)                |                       | 1.83m  |
| Width W (Imperial)               |                       | 3.0"   |
| Width W (Metric)                 |                       | 76.2mm   |
| Width W2 (Imperial)              |                       | 3.0"   |
| Width W2 (Metric)                |                       | 76.2mm   |
| Width W6 (imperial)              |                       | 1.0"   |
| Width W6 (metric)                |                       | 25.4mm   |
| Height H (Imperial)              |                       | 3.07"  |
| Height H (Metric)                |                       | 77.9mm   |
| Mounting Hole Centers (Imperial) |                       | 4.0"   |

181-33000



|                             |                             |                         |
|-----------------------------|-----------------------------|-------------------------|
| Material and Specifications |                             |                         |
|                             | Material                    | Polyvinylchloride (PVC) |
|                             | Material Shortcut           | PVC                     |
|                             | Flammability                | self-extinguishing      |
|                             | Operating Temperature       | +122°F (+50°C)          |
|                             | ROHS Compliant              | Yes                     |
|                             | Certification/Specification | UL                      |
|                             | UL Recognized (US)          | Yes                     |
| Logistic and Packaging      |                             |                         |
|                             | Package Quantity (Imperial) | 120ft                   |
|                             | Package Quantity (Metric)   | 36.6m                   |
|                             | Customs Number(Schedule B)  | 3925900000              |