

# Model #: S410-006

## 6-ft. SCSI Double Shielded Cable (HD50M/HD68M)

#### **Highlights**

- Premium double-shielded cable
- 34 twisted-pair conductors



## Description

Multi-platform SCSI III to II external peripheral cable HD68M/HD50M. This 6ft cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

System Requirements

• Any external SCSI III or II device or controller card requiring HD68 or HD50 interface

Package Includes

• 6-ft. SCSI cable HD68M to HD50M double shielded

#### **Features**

- Multi-platform SCSI III to II external peripheral cable
- HD68M/HD50M, 6-ft.
- Designed to connect two SCSI III or SCSI II devices together
- Constructed using double shielded 34 twisted pair high impedance cable
- Low-capacitance impedance matched 28 AWG stranded tinned copper insulated in polypropylene
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

### **Specifications**

OVERVIEW	
Intended Application	Connecting Drives
Cable Type	SCSI
Model Type	SCSI III External
INPUT	

Cable Length (ft.)	6			
Cable Length (m)	1.83			
UPC Codes				
Unit Carton UPC#	037332014153			
PHYSICAL				
Color	Beige			
Style	SCSI			
CONNECTIONS				
Connector A	• (			
Connector B	(())) HD50 (MALE)			
WARRANTY				
Product Warranty Period (Worldwide)	Lifetime limited warranty			

## **Related Items**

#### **Optional Products**

Related Model	Description	Qty.
S140-000	External SCSI U320 LVD/SE Active Terminator (HD68 M)	1
S450-010	6-ft. SCSI Ultra2/U160/U320 LVD Cable (HD68 M/M w/thumbscrews)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2396.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.