To request the full datasheet, please visit <a href="https://www.intersil.com/products/isl24016">www.intersil.com/products/isl24016</a>

Data Sheet October 8, 2009 FN6540.1

# High Voltage 7-Channel Voltage Level Translator and 2 RRIO Amplifiers

The ISL24016 is a high performance level translator. It consists of 7-Channel inputs and 14-Channel complementary level translated outputs, and 2 general purpose amplifiers. The level translator OUTx and  $\overline{\text{OUTx}}$  complementary outputs are controlled by  $V_{\text{INx}}$  logic input signals. Their output high and low voltage levels are set by REFH and REFL inputs respectively. The level shifter is designed to deliver large peak current into highly capacitive loads. The additional dual general purpose amplifiers can be use to create  $V_{\text{REFH}}$  and  $V_{\text{REFL}}$  voltages.

The ISL24016 is available in a 32 Ld Thermal Enhanced TQFN package. It is specified for operation over the -40°C to +85°C industrial temperature range.

## Ordering Information

PART NUMBER (Note)	PART MARKING	TEMP. RANGE (°C)	PACKAGE (Pb-free)	PKG. DWG.#
ISL24016IRTZ*	ISL240 16IRTZ	-40 to +85	32 Ld TQFN	L32.5x5C

<sup>\*</sup>Add "-T13" suffix for tape and reel. Please refer to TB347 for details on reel specifications

NOTE: These Intersil Pb-free plastic packaged products employ special Pb-free material sets, molding compounds/die attach materials, and 100% matte tin plate plus anneal (e3 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations). Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.


#### **Features**

- 18V Output Range
- · Rail-to-Rail Output Voltage Range
- · 200mA Peak Output Current per Channel
- 45 V/µs Level Translator Slew Rate
- · Dual Rail-to-Rail Input and Output Amplifiers
- · 32 Ld TQFN Package
- · Pb-Free (RoHS compliant)

### **Applications**

- TFT-LCD Panels
- · Logic Level Translator

### **Pinout**



THERMAL PAD CONNECTS TO GND

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9001 quality systems. Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com