

Article Number: 115-41800



Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66, Black, 25/pkg Description:

Base Data		
	Local Order Number	RT250S0X2
	Type	RT250S
	Color	Black (BK)
	Features and Benefits	 Special extended-pawl design offers a release feature for quick and easy access to wire bundles. Head design provides high tensile strength with very low insertion force even after repeated use. Buckle feature on head allows excess strap to be tucked away after installation.
	Quantity Per	bag
	Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66, Black, 25/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	250.0lbs
	Minimum Tensile Strength (Metric)	1115.0N
	Length L (Imperial)	9.1"
	Length L (Metric)	230.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	Yes
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.49"
	Width W (Metric)	12.5mm
	Cable Tie Width Max. (Imperial)	0.49"
	Cable Tie Width Max. (Metric)	12.5mm

generated on: 4/28/2017

115-41800



Bundle Diameter Min. (Imperial)	0.47"
Bundle Diameter Min. (Metric)	12.0mm
Bundle Diameter Max. (Imperial)	2.0"
Bundle Diameter Max. (Metric)	50.0mm
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Minimum Application Temperature	-
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number(Schedule B)	3926909987
	Bundle Diameter Min. (Metric) Bundle Diameter Max. (Imperial) Bundle Diameter Max. (Metric) Material Material Shortcut Flammability Minimum Application Temperature Operating Temperature ROHS Compliant Certification/Specification UL Recognized (US and Canada) Package Quantity (Imperial) Package Quantity (Metric)

generated on: 4/28/2017