



Article Number: 181-15107

Slotted Cable and Wiring Duct, 1.5" x 1", Non-Adhesive, PVC, White, 120 ft/carton Description:

Base Data		
	Local Order Number	181-15107
	Туре	SL1.5X1
	Color	White (WH)
	Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li> </ul>
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1.5" x 1", Non-Adhesive, PVC, White, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	0.75"
	Width W5 (metric)	19.1mm

generated on: 4/28/2017

## 181-15107



Product Dimensions         Height H (Metric)         26.9mm           Material and Specifications Specifications Specifications Alexander and Packaging Package Quantity (Imperial)         Material Polyvinylchloride (PVC)           Material Shortcut PVC Flammability Pore and Package Quantity (Imperial)         PVC			
Height H (Metric)   26.9mm     Mounting Hole Centers (Imperial)   4.0"     Material and Specifications   Material Shortcut   PVC     Material Shortcut   PVC     Flammability   self-extinguishing     Operating Temperature   +122°F (+50°C)     ROHS Compliant   Yes     Certification/Specification   CSA     UL Recognized (US)   Yes     Logistic and Packaging     Package Quantity (Imperial)   120ft     Package Quantity (Metric)   36.6m		Height H (Imperial)	1.06"
Material and Specifications Period Polyvinylchloride (PVC)  Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Height H (Metric)	26.9mm
Specifications  Material  Material  Material Shortcut  Flammability  Operating Temperature  ROHS Compliant  Certification/Specification  UL Recognized (US)  Package Quantity (Imperial)  Package Quantity (Metric)  Polyvinylchloride (PVC)  PVC  PVC  Flammability  self-extinguishing  +122°F (+50°C)  CSA  CSA  UL Recognized (US)  Yes  Package Quantity (Imperial)  120ft  Package Quantity (Metric)  36.6m		Mounting Hole Centers (Imperial)	4.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m			
Flammability  Operating Temperature  +122°F (+50°C)  ROHS Compliant  Yes  Certification/Specification  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  Self-extinguishing  +122°F (+50°C)  Yes  CSA  USA  UL Recognized (US)  Yes  120ft  Package Quantity (Metric)  36.6m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification CSA  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 120ft  Package Quantity (Metric) 36.6m		Material Shortcut	PVC
ROHS Compliant  Certification/Specification  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  Package Quantity (Metric)  Yes  Logistic and Package Quantity (Imperial)  120ft  Package Quantity (Metric)  36.6m		Flammability	self-extinguishing
Certification/Specification UL Recognized (US)  Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  CSA  Yes  120ft Package Quantity (Metric)  36.6m		Operating Temperature	+122°F (+50°C)
Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  Package Quantity (Metric)  Yes  120ft Package Quantity (Metric)  36.6m		ROHS Compliant	Yes
Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  120ft Package Quantity (Metric)  36.6m		Certification/Specification	CSA
Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  120ft  Package Quantity (Metric)  36.6m		UL Recognized (US)	Yes
Package Quantity (Metric) 36.6m			
		Package Quantity (Imperial)	120ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	36.6m
		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017