

553-50063

# HellermannTyton

Article Number: 553-50063

Description: Heat Shrink Labels, .125" (3.17mm), Single Sided, 3-Slit, PO-X, White, 1000/box



| Base Data                        |   |
|----------------------------------|---|
| Local Order Number               | 553-50063   |
| Type                             | HST3-1WH-3S   |
| Color                            | White (WH)  |
| Features and Benefits            | <ul style="list-style-type: none"> <li>• Slide Slit and optional center slits for easy wire insertion.</li> <li>• Smooth surface for clean and legible printing.</li> <li>• Supplied on a ladder style carrier so that markers can be kitted after printing.</li> <li>• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.</li> </ul>  |
| Quantity Per                     | box   |
| Product Description              | HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production. |
| Short Description                | Heat Shrink Labels, .125" (3.17mm), Single Sided, 3-Slit, PO-X, White, 1000/box   |
| Product Dimensions               |   |
| Length L (Imperial)              | 0.475"  |
| Length L (Metric)                | 12.0mm  |
| Printable (Yes/No)               | Yes   |
| Variant                          | Thin-Wall   |
| Width W (Imperial)               | 0.475"  |
| Width W (Metric)                 | 12.0mm  |
| Height H (Imperial)              | 0.235"  |
| Height H (Metric)                | 5.97mm  |
| Diameter Max. (Imperial)         | 0.125"  |
| Outside Diameter Max. (Imperial) | 0.125"  |
| Outside Diameter Max. (Metric)   | 3.2mm   |
| Wall Thickness WT (Imperial)     | 0.0209"   |
| Wall Thickness WT (Metric)       | 0.53mm  |

553-50063



|                             |                                    |                                   |
|-----------------------------|------------------------------------|-----------------------------------|
| Product Dimensions          | Flexibility                        | Flexible                          |
|                             | Print Method                       | Thermal transfer                  |
|                             | Recovered Diameter d (metric)      | 1.1mm                             |
|                             | Recovered Diameter d (imperial)    | 0.043"                            |
|                             | Supplied Diameter D (imperial)     | 0.118"                            |
|                             | Supplied Diameter D (metric)       | 3.0mm                             |
|                             | Thickness T (Metric)               | 3.0µm                             |
|                             | Width of Liner WL (imperial)       | 3.0"                              |
|                             | Width of Liner WL (metric)         | 76.2mm                            |
|                             | Width of Printable Area (imperial) | 0.475"                            |
|                             | Width of printable area (metric)   | 12.07mm                           |
| Material and Specifications |                                    |                                   |
|                             | Material                           | Polyolefin, cross-linked (PO-X)   |
|                             | Material Shortcut                  | PO-X                              |
|                             | US MILSPEC                         | AMS-DTL-23053/5 Class 1 and 3     |
|                             | Dielectric Strength (Metric)       | 19.7 kV min.                      |
|                             | Flammability                       | UL 224 VW-1                       |
|                             | Shrink Temperature                 | +194 °F (+90 °C)                  |
|                             | Operating Temperature              | -67°F to +275°F (-55°C to +135°C) |
|                             | REACH Compliant (Article 33)       | Yes                               |
|                             | ROHS Compliant                     | Yes                               |
| Certification/Specification | CEN                                |                                   |
| Logistic and Packaging      |                                    |                                   |
|                             | Package Quantity (Imperial)        | 1000                              |
|                             | Package Quantity (Metric)          | 1000                              |
|                             | Customs Number(Schedule B)         | 3926909987                        |
|                             | Markers per row                    | 4                                 |
|                             | Content Unit (BMEcat)              | pack                              |
|                             | Weight (imperial)                  | 2.57                              |
| Weight (Metric)             | 1.176kg                            |                                   |