HellermannTyton



Article Number: 157-00401

Description: Wide Strap Cable Tie with .25" Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

| Base Data | | |
|-----------------------|-------------------------------------|--|
| | Local Order Number | 157-00401 |
| | Туре | WSI250 |
| | Color | Black (BK) |
| | Features and Benefits | Mount provides low insertion and high extraction forces which makes for a strong and easy installation. Clamping rails increase grip on round bundles. Thinner strap provides increased flexibility for improved ergonomics. Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability. |
| | Quantity Per | bag |
| | Product Description | Wide Strap Heavy Duty Cable Ties features a stud mount for direction application onto a 1/4" threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 4.2". The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. |
| | Short Description | Wide Strap Cable Tie with .25" Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag |
| Product Dimensions | | |
| | Minimum Tensile Strength (Imperial) | 120.0lbs |
| | Minimum Tensile Strength (Metric) | 534N |
| | Length L (Imperial) | 12.7" |
| | Length L (Metric) | 322.6mm |
| | Fixation Method | Weld Stud Fixing |
| | Identification Plate Position | none |
| | Releasable Closure | No |
| | Tie Closure | plastic pawl |
| | Variant | Inside Serrated |
| | Width W (Imperial) | 0.5" |
| | Width W (Metric) | 12.7mm |
| | Bundle Diameter Min. (Imperial) | 0.38" |
| | Bundle Diameter Min. (Metric) | 9.5mm |

157-00401

HellermannTyton

| Product Dimensions | Bundle Diameter Max. (Imperial) | 3.2" |
|--------------------------------|---------------------------------|--|
| | Bundle Diameter Max. (Metric) | 82.5mm |
| | Stud Size (Imperial) | 0.25" |
| | Stud Size (Metric) | 6.35 mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| | Material Shortcut | PA66HIRHSUV |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 300 |
| | Package Quantity (Metric) | 300Bag |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |