

170-03194



Article Number: 170-03194

Description: Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .75" Dia, AL/GF, Silver, 15/box

| | | |
|-----------------------------|------------------------------|--|
| Base Data | Local Order Number | 170-03194 |
| | Type | BSHTTSW34SB |
| | Color | Silver (SR) |
| | Features and Benefits | <ul style="list-style-type: none"> • A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application. |
| | Quantity Per | box |
| | Product Description | Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. |
| | Short Description | Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .75" Dia, AL/GF, Silver, 15/box |
| | | |
| Product Dimensions | Length L (Imperial) | 4.0ft |
| | Length L (Metric) | 1.22m |
| | Reel Length (imperial) | 4.0ft |
| | Diameter D (imperial) | 0.75" |
| | Diameter D (metric) | 19.05mm |
| | Nominal Diameter (Imperial) | 3/4" |
| | Nominal Diameter (Metric) | 19.05mm |
| | Wall Thickness WT (Imperial) | .042" |
| | Wall Thickness WT (Metric) | 1.06mm |
| | | |
| Material and Specifications | Material | Glass fiber with aluminium foil (GF-AL) |
| | Material Shortcut | GF-AL |
| | | |

170-03194



| | | |
|-----------------------------|-----------------------------|-----------------------------------|
| Material and Specifications | Flammability | non flammable |
| | Operating Temperature | -76°F to +491°F (-60°C to +255°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 15 |
| | Package Quantity (Metric) | 15 |
| | Customs Number(Schedule B) | 7019901000 |