



Datasheet for part number FRCIR06F36A-48PF80T108VO

|   |
|---|
| Our Catalog Part Number: FRCIR06F-36-A48P-F80-T108-V0   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|   |  |
|---|--|
| Product Datasheet                                     |  |
| SERIES  | Connector with Bayonet Coupling  |
| Shell Style   | Straight Plug Connector  |
| Environmental Class                                   | Backshell with A style clamp and bushing but includes wire sealing grommet and compression ring.   |
| Shell Size  | 36   |
| Contact Arrangement                                   | 36A-48   |
| Total Number of contacts                              | 48 contacts  |
| Number of Contacts Size 16                            | 48 contacts size 16  |
| Gender  | Pin  |
| Contact Type  | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                       | Gold   |
| Shell Material  | Aluminium alloy  |
| Shell Plating   | Zinc/Cobalt black trivalent passivation (conductive)   |
| Contacts included                                     | no, delivery without contacts  |
| Shock Resistance                                      | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling  | 2000 couplings minimum   |
| Service Rating Letter                                 | I  |
| Operating Voltage DC                                  | 250 V  |
| Operating Voltage AC                                  | 200 V  |
| Dielectric strength -<br>Minimum Flashover AC RMS     | 1400 V   |
| Dielectric strength -<br>Test Voltage AC RMS (Hi Pot) | 1000 V   |
| Note  | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General   | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |