

Article Number: 161-64216

ererer

Description: Helawrap, HWPP16, 5/8" (16mm) Dia, PP, White, 100

ft/reel

Base Data		
	Local Order Number	161-64216
	Туре	HWPP16
	Color	White (WH)
	Features and Benefits	 Unique open design for easy branch-offs at any point along the harness. Overwrap formation provides abrasion protection and accommodates multiple bundle configurations. Flexible construction and design eliminates pinch points and minimizes bending fatigue, making it ideal for applications involving movement and vibration. Split shape allows for future access without disassembly.
	Quantity Per	reel
	Product Description	The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.
	Short Description	Helawrap, HWPP16, 5/8" (16mm) Dia, PP, White, 100 ft/reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.48m
	Reel Length (imperial)	100.0ft
	Variant	Spiral Binding
	Bundle Diameter Min. (Imperial)	0.51"
	Bundle Diameter Min. (Metric)	12.95mm
	Bundle Diameter Max. (Imperial)	0.63"
	Bundle Diameter Max. (Metric)	16.0mm
	Diameter D (imperial)	0.5"
	Diameter D (metric)	12.70mm
	Nominal Diameter (Imperial)	5/8"
	Nominal Diameter (Metric)	16.0mm

generated on: 4/28/2017

161-64216



Product Dimensions Di			
Pitch (imperial) 0.51" Pitch (metric) 12.95mm Material and Specifications Material Shortcut PP Flammability UL 94 HB Halogenfree Yes Operating Temperature -76°F to +230°F (-60°C to +110°C) ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) 100ft Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 1.55 bs		Wall Thickness WT (Imperial)	0.03"
Pitch (metric) 12.95mm		Wall Thickness WT (Metric)	0.8mm
Material and Specifications Polypropylene (PP) Material Shortcut PP Flammability UL 94 HB Halogenfree Yes Operating Temperature -76°F to +230°F (-60°C to +110°C) ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) 100ft Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs		Pitch (imperial)	0.51"
Specifications Material Material Shortcut PP Flammability Halogenfree Operating Temperature ROHS Compliant Ves Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) Polypropylene (PP) PU PU PU PU PP PU UL 94 HB Pe Ves Operating Temperature -76°F to +230°F (-60°C to +110°C) Yes Pu Pu Pu Pu Pu Pu Pu Pu Pu P		Pitch (metric)	12.95mm
Material Shortcut PP Flammability UL 94 HB Halogenfree Yes Operating Temperature -76°F to +230°F (-60°C to +110°C) ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) 100ft Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs			
Flammability Halogenfree Ves Operating Temperature ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) UL 94 HB Yes 1-76°F to +230°F (-60°C to +110°C) Yes 100ft 30.48m 2.55lbs		Material	Polypropylene (PP)
Halogenfree Yes Operating Temperature -76°F to +230°F (-60°C to +110°C) ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) 100ft Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs		Material Shortcut	PP
Operating Temperature -76°F to +230°F (-60°C to +110°C) ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) 100ft Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs		Flammability	UL 94 HB
ROHS Compliant Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) Yes 100ft 30.48m 2.55lbs		Halogenfree	Yes
Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.55lbs		Operating Temperature	-76°F to +230°F (-60°C to +110°C)
Packaging Package Quantity (Imperial) Package Quantity (Metric) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.55lbs		ROHS Compliant	Yes
Package Quantity (Metric) 30.48m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs			
Customs Number(Schedule B) 3926909987 Weight (imperial) 2.55lbs		Package Quantity (Imperial)	100ft
Weight (imperial) 2.55lbs		Package Quantity (Metric)	30.48m
		Customs Number(Schedule B)	3926909987
Weight (Metric) 1.16kg		Weight (imperial)	2.55lbs
		Weight (Metric)	1.16kg

generated on: 4/28/2017