

Article Number: 181-12010



Description: Slotted Cable and Wiring Duct, 1" x 2", Adhesive, PVC,

Gray, 30ft/box

Base Data		
	Local Order Number	181-12010
	Туре	SLA1X2
	Color	Gray (GY)
	Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	box
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1" x 2", Adhesive, PVC, Gray, 30ft/box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.62"
	Width W5 (metric)	41.1mm

generated on: 4/28/2017

181-12010



Product Dimensions Height H (Imperial) 2.07" Height H (Metric) 52.6mm Mounting Hole Centers (Imperial) 4.0" Material and Specifications Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL
Height H (Metric) Mounting Hole Centers (Imperial) Material and Specifications Material Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability Operating Temperature H122°F (+50°C) ROHS Compliant Yes
Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes
Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes
Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes
Operating Temperature +122°F (+50°C) ROHS Compliant Yes
ROHS Compliant Yes
Certification/Specification III
Oct uncation/opecinication
UL Recognized (US) Yes
Logistic and Packaging
Package Quantity (Imperial) 30.0ft
Package Quantity (Metric) 9.1m
Customs Number(Schedule B) 3925900000

generated on: 4/28/2017