



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: ULTRACOPY

### Isobar Surge Suppressor - Direct plug-in surge, spike and line noise protection

#### Highlights

- 2 outlets (20-amp)/direct plug-in
- 600 joule rating
- All-metal housing with LEDs
- \$10,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 15 million satisfied customers, the Isobar remains the world's #1 selling premium surge suppressor. Loaded with a generous combination of high-quality components, near indestructible all-metal case and unique noise filtration system, Isobars offer the highest level of protection. Robust surge suppression circuits with sine wave tracking offer extreme levels of protection against the heaviest surge conditions. Isobar's unique protection system combines large torroidal chokes, HF/VHF capacitors and multiple metal oxide varistors that remove high-level surges and EMI/RFI interference. UltraCopy features two 20A-style outlets arranged with standard wall socket spacing in a cordless direct plug-in format. Mounting tabs allow permanent connection via duplex switchplate screw. Surge suppression rated at 600 joules/48,000 amps provides high-grade protection. Diagnostic LEDs confirm power availability, line fault and protection status. Lifetime warranty with \$10,000 [Ultimate Lifetime Insurance](#) for connected equipment (USA, Puerto Rico & Canada Only).

PLUG/OUTLETS: Input NEMA 5-20P; Output 2 NEMA 5-20R

ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-20R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/600 joules/48,000 amps

FORMAT: Direct plug-in, receptacle mount form factor

#### Applications

- Ideal for premium AC protection for sensitive electronics with either 15A or 20A input plugs, including photocopiers, personal computers with peripherals, network and CAD/CAM/CAE workstations, internetworking accessories, telecommunications systems, point-of sale-equipment, audio/video and home theater systems in any home, office or industrial application

#### Package Includes

- ULTRACOPY Surge Suppressor
- Instruction manual with warranty information

#### Features

- Tripp Lite's ISOBAR is the world's #1 selling premium suppressor series with more than 15 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications
- Multi-component suppression circuits combine torroidal chokes, HF/VHF capacitors and metal oxide varistors
- 2 outlets with standard duplex wall outlet spacing offer convenient wall receptacle mount placement; included mounting tab allows permanent connection via wall receptacle switch plate screw.

- Heavy-grade surge suppression rated at 600 joules/48,000 amps
- 3 LED indicators confirm suppressor operation and site wiring status, plus warning of suppressor or electrical fault conditions
- 120V AC, 50/60Hz, 20A electrical compatibility
- \$10,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada Only)
- Lifetime product warranty
- UL1449 listed surge suppression (330V let-through), UL1283 listed EMI protection, UL1363 listed power tap, cUL approved to Canadian standards

## Specifications

<b>OUTPUT</b>	
Frequency compatibility	50 / 60 Hz
Output watts	2400
Circuit Breaker (amps)	20
Outlet quantity / type	2 NEMA 5-20R
<b>INPUT</b>	
Recommended Electrical Service	120V, 20A
Input connection type	NEMA 5-20P input plug
Input cord length details	Direct plug-in
Voltage compatibility (VAC)	120
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	600
AC suppression response time	NM = 0 ns. CM =
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping voltage (RMS)	140
AC suppression surge current rating	48,000 amps
AC suppression components used	Metal oxide varistors, toroidal balanced chokes and VHF capacitors
Safe thermal fusing	Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurrences
EMI / RFI filtering	40-80 dB
Immunity	Conforms to IEE 587 / ANSI C62.41
<b>UPC Codes</b>	
Unit Carton UPC#	037332010513
<b>PHYSICAL</b>	
Unit Dimensions (HWD/in)	4 x 2.5 x 2.5
Unit Dimensions (HWD/cm)	10.2 x 6.4 x 6.4
Material of construction	Metal

<b>Receptacle Color</b>	Black
<b>Form factors supported</b>	Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Attractive, all-black metal direct plug-in suppressor
<b>CERTIFICATIONS</b>	
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449
<b>UL1283 (EMI Filter)</b>	UL1283
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$10,000 <a href="#">Ultimate Lifetime Insurance</a>

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=95](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=95).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.