

156-00068

Article Number: 156-00068

Description: Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"-.26" Panel Thickness, PA66HIRHSUV, Black,100/pkg



Base Data	Local Order Number	156-00068
	Type	WSSFT9A
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • The "H" profile provides a broad surface contact to minimize the pinching of bundles. • Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation. • Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.
	Short Description	Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"-.26" Panel Thickness, PA66HIRHSUV, Black,100/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		534N
Length L (Imperial)		9.0"
Length L (Metric)		228.0mm
Fixation Method		Fir Tree
Identification Plate Position		none
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.5"
Width W (Metric)		12.7mm
Width W2 (Imperial)		0.51"
Width W2 (Metric)		13.0mm
Height H (Imperial)		0.75"

156-00068



Product Dimensions	Height H (Metric)	19.1mm
	Height H2 (Imperial)	0.36"
	Height H2 (Metric)	9.0mm
	Bundle Diameter Max. (Imperial)	2.3"
	Bundle Diameter Max. (Metric)	57.0mm
	Disc Diameter (Imperial)	0.9"
	Disc Diameter (Metric)	21.6mm
	Panel Thickness Max. (Imperial)	0.26"
	Panel Thickness Max. (Metric)	6.5mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	1.0mm
	Mounting Hole Diameter D (Metric)	8.75 - 9.25 mm
	Mounting Hole Diameter D Min. (Imperial)	0.34"
	Mounting Hole Diameter D Max. (Imperial)	0.36"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Flammability	UL 94 HB
	Operating Temperature	-65°F to +212°F (-54°C to +100°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	6.4kg