

596-00326

HellermannTyton

Article Number: 596-00326

Description: Solar Label, BIPOLAR SOLAR ARRAY, 3.75" x 2.0", VL, Red, 50/pkg



Base Data	Local Order Number	596-00326
	Type	BIPOLARPV
	Color	Red (RD)
	Features and benefits	<ul style="list-style-type: none"> • Made with UV stable inks and materials for durability and weather resistance. • The labels are supplied with aggressive adhesive to ensure long life. • Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, 3.75" X 2", BIPOLAR SOLAR ARRAY, Red
	Short Description	Solar Label, BIPOLAR SOLAR ARRAY, 3.75" x 2.0", VL, Red, 50/pkg
Product Dimensions	Width W (Imperial)	3.75"
	Width W (Metric)	92.25mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
Material and Specifications	Material	Vinyl
	Material Shortcut	VL
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	Halogenfree	Yes

596-00326



Material and Specifications	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060