

112-51905



Article Number: 112-51905

Description: Clamp Tie, 4" Long, 20lb Tensile Strength, PA66HS, Black, 100/pkg

Base Data	Local Order Number	CTT20R0HSC2
	Type	CTT20R
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Heat stabilized cable ties provide excellent resistance to high heat exposures. • Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
	Quantity Per	bag
	Product Description	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Clamp Tie, 4" Long, 20lb Tensile Strength, PA66HS, Black, 100/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		90N
Length L (Imperial)		4.0"
Length L (Metric)		101.6mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.1"
Width W (Metric)		2.5mm
Bundle Diameter Min. (Imperial)		0.06"
Bundle Diameter Min. (Metric)		1.6mm

112-51905



Product Dimensions	Bundle Diameter Max. (Imperial)	0.51"
	Bundle Diameter Max. (Metric)	13.0mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987