

598-00022

HellermannTyton

Article Number: 598-00022

Description: Handi-Card Wire and Cable Markers, .25" x 1.5", Solid #2, 36 Per Card, TYHC, White, 25/pkg



Base Data	
Local Order Number	TYHC2
Type	TYHC2
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Handi-Cards have a split backing so that a portion of the liner can be removed to expose the markers for easy dispensing. • Handi-Cards are kitted on the card so that specific markers can be removed without affecting the other markers on the card. • Markers are pre-printed so no additional post printing is required, saving time and money. • Label material is a conformable cloth that ensures markers stay on wires and cables for the life of the application.
Quantity Per	pack
Product Description	HellermannTyton Handi-Cards are easy release pre-printed cloth markers, on a plastic card, with a strong adhesive for a long lasting bond on wire and cable. The markers are available in Solid format where each marker on the card contains the same legend and Sequence format where each marker on the card contains a different number or letter which is usually printed in sequence from lowest to highest in sort order.
Technical Description	Handi-Card, .25" X 1.5", Solid #2, 36 Per Card, White
Short Description	Handi-Card Wire and Cable Markers, .25" x 1.5", Solid #2, 36 Per Card, TYHC, White, 25/pkg
Product Dimensions	
Length L (Imperial)	1.5"
Length L (Metric)	38.1mm
Width W (Imperial)	0.25"
Width W (Metric)	6.35mm
Height H (Imperial)	1.5"
Height H (Metric)	38.1mm
Bundle Diameter Min. (Imperial)	0.13"
Bundle Diameter Min. (Metric)	3.40mm
Bundle Diameter Max. (Imperial)	0.29"
Bundle Diameter Max. (Metric)	7.50mm

598-00022



Product Dimensions	Outside Diameter Min. (Imperial)	0.13"
	Outside Diameter Min. (Metric)	3.40mm
	Outside Diameter Max. (Imperial)	0.29"
	Outside Diameter Max. (Metric)	7.50mm
Material and Specifications		
	Material	Vinyl Cloth (TYHC)
	Material Shortcut	TYHC
	Adhesive	Rubber
	Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	5903103000
	Labels per Column	1
	Labels per Row	36
	Labels per Sheet	36