

596-00257

Article Number: 596-00257

Description: Solar Marker, Reflective, Non-Adhesive, PV POWER SOURCE, 6.75" x 2.75", VL, Red, 1/pkg



Base Data	Local Order Number	596-00257
	Type	PVPSRTM
	Color	Red (RD)
	Features and benefits	<ul style="list-style-type: none"> <li>• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.</li> <li>• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.</li> <li>• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.</li> <li>• The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.</li> </ul>
	Quantity Per	EA
	Product Description	Designed to meet NEC2014 and NEC2017 Section 690.4(F) as interpreted by the International Association of Electrical Inspectors (IAEI,) HellermannTyton offers an aluminum and vinyl label designed for use on almost any type of roof shingle. Mount via a pre-cut aluminum plate with aluminum clips (both supplied with label) to standard tar shingles; or bend, shape and fasten with construction adhesive or grommet screws on composite or wooden roofing. Label text is reflective to meet IFC requirements.
	Technical Description	Pre-Printed Solar Label, Reflective, Roof Top Label, 6.75" X 2.75", PV POWER SOURCE, Red
	Local Order Number 2	Spanish Version: 596-00822
	Short Description	Solar Marker, Reflective, Non-Adhesive, PV POWER SOURCE, 6.75" x 2.75", VL, Red, 1/pkg
Product Dimensions	Length L (Imperial)	6.75"
	Length L (Metric)	171.4mm
	Width W (Imperial)	6.75"
	Width W (Metric)	171.4mm
	Height H (Imperial)	2.75"
	Height H (Metric)	69.85mm

596-00257



Material and Specifications		
	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	IFC 2012
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1