APPLICA	BLE STAN	DARD									
OPERATING TEMPERATURE RANGE		-35°C TO 85°C(NOTE	ES 1)	STORAGE TEMPERA	: TURE RAN	GE	-10°C TO 60°C				
RATING	RATING VOLTAGE		30V AC	APPLIC, CONNE				DF40*-*DP-0. 4			
CURRENT		0. 3A									
SPECIFICATIONS											
٦	ГЕМ		TEST METHOD			1	REQU	IREMENTS	QT	AT	
	RUCTION								ΤX		
			LY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.				X	
			RMED VISUALLY.						X	<u> </u>	
ELECTRIC CHARACTER CONTACT RESISTANCE 20mV						180mΩ MAX.					
INSULATIO		100V DC.				 50MΩ MIN.				 - -	
RESISTANCE		100V DC.				OUNIS 2 IVIIIN.				-	
VOLTAGE PROOF		100V AC FOR 1 min.			NO F	NO FLASHOVER OR BREAKDOWN.					
MECHANICAL CHARACTERISTICS											
MECHANICAL OPERATION		3000TIMES INSERTIONS AND EXTRACTIONS.			2 N	 CONTACT RESISTANCE: 180mΩ MAX. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				_	
COUN	IT DI	ESCRIPTIO	ON OF REVISIONS		DESIGNED			CHECKED	D	ATE	
Δ											
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT						APPRO	OVED	KH. IKEDA	08.	04. 28	
THE TENT ENATORE			MOINS DI SOMMENI			CHEC		TS. MIYAZAKI	+	08. 04. 28	
Unless otherwise specified, refer			to JIS C 5402.			DESIG DRAV		TK. SUZUK I TK. SUZUK I	08. 04. 25 08. 04. 25		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAW	DRAWING NO.		ELC4-315629-02			
RS SPECIFICATION SHEET PART					PART NO.	O. DF40JC-*DS-0. 4V (53)					
	HIR	OSE EI	OSE ELECTRIC CO., LTD.				CL684 🛕			1/1	