MALLORY Mallory Sonalert Products, Inc. Part #: SCE120XA3DP3B Revision: **Sales Outline Drawing Specifications:** Sound Level Category Extra Loud Fast Double Beep @ .5 PPS Mode of Operation Voltage Rating 48 to 120 VAC Frequency 2900 ± 500 Hz Loudness @ 2 FT 95 to 105 Typ. **Current Draw** 40mA MAX Housing Material 6/6 Nylon, Color: Black Storage Temperature -40° to +85° C Operating Temperature -40° to +85° C Panel Mounting Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. Knurled Nut Used to attach part to panel. The max recommended torque is 10 in-lbs. Weight (Typical) 1.6 oz (45g) NEMA 3R,4X, & 12 Approved with use of ACC03. Please contact factory. Options **Dimensions:** Inches (mm) 1,687±.005 [42,85±.13] MALLORY 1.210 1.240 0 0 SOCKET (5mm Pin Spacing) 1 1/8-24 UNS 2A THD. -KNURLED NUT -PLUGGABLE SCREW 1,313±.005 [33,34±.13] TERMINAL BLOCK .375±.005 [9,52±.13] $.47\pm.01$ [11,94±.25] - .031±.005 [,79±.13] 1.41±.1 [35.85±2.54]