

Article Number: 596-00405

Description: Foam Nameplate, 1.2" x 1.5" Button Label With .88" Hole,

PET, Yellow, 250/roll

HellermannTyton

Base Data		
	Local Order Number	596-00405
	Туре	NPLH31X38YE22.5
	Color	Yellow (YE)
	Features and benefits	<ul> <li>Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.</li> <li>Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.</li> <li>Labels are UV and chemical resistant for long life in an industrial environment.</li> <li>Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.</li> </ul>
	Quantity Per	reel
	Product Description	Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.
	Technical Description	Foam Nameplate, 1.2" X 1.5" Button Label With .88" Hole, PET, Yellow
	Short Description	Foam Nameplate, 1.2" x 1.5" Button Label With .88" Hole, PET, Yellow, 250/roll
Product Dimensions		
	Length L (Imperial)	1.5"
	Length L (Metric)	38.1mm
	Self adhesive (Yes/No)	Yes
	Width W (Imperial)	1.2"
	Width W (Metric)	30.5mm
	Height H (Imperial)	1.5"
	Height H (Metric)	38.1mm
	Mounting Hole Diameter D (Imperial)	0.88"
	Mounting Hole Diameter D (Metric)	22.35 mm
	Horizontal Repeat HR (imperial)	1.2"
	Horizontal Repeat HR (metric)	30.5mm

generated on: 4/29/2017

## 596-00405



Product Dimensions	Print Method	Thermal transfer
	Vertical Repeat VR (imperial)	1.625"
	Vertical Repeat VR (metric)	41.27mm
	Width of Liner WL (imperial)	1.45"
	Width of Liner WL (metric)	36.83mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +176°F (-40°C to +80°C)
	Operating Temperature	-40°F to +176°F (-40°C to +80°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	250ft
	Package Quantity (Metric)	76.2m
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1

generated on: 4/29/2017