Search Entire Site Contact IDT | Investors | Press

About IDT Products Applications Support

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > > 952911 > 952911BFT

Add to myIDT [?]

You may also like...

myIDT

952911BFT

DIDT

Category:

952911 Generic Part: Market Group: PC CLOCK Description: PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: • 2 - 0.7V current-mode differential CPU pairs • 10 - PCI, 3 free running, 33MHz • 3 - REF, 14.318MHz • 3 - 3V66, 66.66MHz • 1 - 48MHz • 1 -

24/48MHz • 2 - 25MHz @ 2.5V



Parameters

Package	SSOP 48 (PV48)
Speed	NA
Temperature	С
Voltage	3.3 V
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 48LD	
Class	PLASTIC	
Moisture Sensitivity Level (MSL)	1	
Category	Standard	
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH	
Peak Reflow Temprature	225°C	
Rebake Conditions	N/A	
Length	15.9	
Mark	F	
Width	7.5	
Pitch	0.64	
Thickness	2.3	
Status	Active	