

184-15303

HellermannTyton

Article Number: 184-15303

Description: Slotted Cable and Wiring Duct, High-Density, 1.5" x 3",
Non-Adhesive, PVC, White, 30ft/box**HellermannTyton**

| Base Data | |
|-----------------------|---|
| Local Order Number | 184-15303 |
| Type | SLHD1.5X3 |
| Color | White (WH) |
| Features and Benefits | <ul style="list-style-type: none"> • Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. • Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. • Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation. |
| Quantity Per | box |
| Product Description | Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| Technical Description | Non-Adhesive |
| Short Description | Slotted Cable and Wiring Duct, High-Density, 1.5" x 3", Non-Adhesive, PVC, White, 30ft/box |
| Product Dimensions | |
| Length L (Imperial) | 6.0ft |
| Length L (Metric) | 1.83m |
| Width W (Imperial) | 1.5" |
| Width W (Metric) | 38.1mm |
| Width W2 (Imperial) | 1.5" |
| Width W2 (Metric) | 38.1mm |
| Width W3 (Imperial) | 0.16" |
| Width W3 (Metric) | 4.1mm |
| Width W4 (imperial) | 0.4" |
| Width W4 (metric) | 10.2mm |
| Width W5 (imperial) | 2.6" |
| Width W5 (metric) | 66.0mm |

184-15303


 The logo for HellermannTyton, with "Hellermann" in blue and "Tyton" in red.

| | | |
|-----------------------------|----------------------------------|-------------------------|
| Product Dimensions | Height H (Imperial) | 3.07" |
| | Height H (Metric) | 77.9mm |
| | Mounting Hole Centers (Imperial) | 2.0" |
| Material and Specifications | | |
| | Material | Polyvinylchloride (PVC) |
| | Material Shortcut | PVC |
| | Flammability | self-extinguishing |
| | Operating Temperature | +122°F (+50°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL |
| | UL Recognized (US) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 30.0ft |
| | Package Quantity (Metric) | 9.1m |
| | Customs Number(Schedule B) | 3925900000 |