CZT5401E

ENHANCED SPECIFICATION SURFACE MOUNT PNP SILICON TRANSISTOR



APPLICATIONS:

- General purpose switching and amplification
- Telephone applications



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CZT5401E is a PNP Silicon Transistor, packaged in an SOT-223 case, designed for general purpose amplifier applications requiring high breakdown voltage.

MARKING: FULL PART NUMBER

FEATURES:

- High Collector Breakdown Voltage 250V
- Low Leakage Current 50nA MAX
- Low Saturation Voltage 150mV MAX @ 50mA
- Complementary Device: CZT5551E
- SOT-223 Surface Mount Package

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
♦ Collector-Base Voltage	V _{CBO}	250	V
♦ Collector-Emitter Voltage	V _{CEO}	220	V
♦ Emitter-Base Voltage	V_{EBO}	7.0	V
Continuous Collector Current	I _C	600	mA
Power Dissipation	P_{D}	2.0	W
Operating and Storage Junction Temperature	T _{J,} T _{stg}	-65 to +150	°C
Thermal Resistance	ΘΙΔ	62.5	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I _{CBO}	V _{CB} =120V		50	nA
I _{CBO}	V _{CB} =120V, T _A =100°C		50	μΑ
I _{EBO}	V _{EB} =3.0V		50	nA
♦ BV _{CBO}	I _C =100μA	250		V
♦ BV _{CEO}	I _C =1.0mA	220		V
♦ BV _{EBO}	I _E =10μA	7.0		V
♦ V _{CE(SAT)}	I _C =10mA, I _B =1.0mA		100	mV
♦ V _{CE(SAT)}	I _C =50mA, I _B =5.0mA		150	mV
V _{BE(SAT)}	I _C =10mA, I _B =1.0mA		1.00	V
V _{BE} (SAT)	I _C =50mA, I _B =5.0mA		1.00	V

♦ Enhanced specification

CZT5401E

ENHANCED SPECIFICATION SURFACE MOUNT







ELECTRICAL CHARACTERISTICS - Continued: (T_A=25°C unless otherwise noted)

	' Д		,	
SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
♦ h _{FE}	V _{CE} =5.0V, I _C =1.0mA	100		
♦ h _{FE}	V _{CE} =5.0V, I _C =10mA	100	300	
♦ h _{FE}	V _{CE} =5.0V, I _C =50mA	75		
♦ h _{FE}	V _{CE} =10V, I _C =150mA	25		
f_T	V _{CE} =10V, I _C =10mA, f=100MHz	100	300	MHz
C_{ob}	V_{CB} =10V, I_E =0, f=1.0MHz		6.0	pF
h _{fe}	V_{CE} =10V, I_{C} =1.0mA, f=1.0kHz	40	200	
NF	V_{CE} =5.0V, I_{C} =200 μ A, R_{S} =10 Ω ,			
	f=10Hz to 15.7kHz		8.0	dB

[♦] Enhanced specification

SOT-223 CASE - MECHANICAL OUTLINE





DIMENSIONS				
INCHES		MILLIMETERS		
MIN	MAX	MIN	MAX	
0°	10°	0°	10°	
0.059	0.071	1.50	1.80	
0.018		0.45		
0.000	0.004	0.00	0.10	
15°		15°		
0.009	0.014	0.23	0.35	
0.248	0.264	6.30	6.70	
0.114	0.122	2.90	3.10	
0.130	0.146	3.30	3.70	
0.264	0.287	6.70	7.30	
0.024	0.033	0.60	0.85	
0.091		2.	30	
0.181		4.	60	
	INC MIN 0° 0.059 0.018 0.000 1: 0.009 0.248 0.114 0.130 0.264 0.024	INCHES MIN MAX 0° 10° 0.059 0.071 0.018 0.000 0.004 15° 0.009 0.014 0.248 0.264 0.114 0.122 0.130 0.146 0.264 0.287 0.009 0.0091 0.181	NCHES MILLIM	

SOT-223 (REV: R3)

LEAD CODE:

- 1) Base 2) Collector
- 3) Emitter
- 4) Collector

MARKING:

FULL PART NUMBER

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- · PbSn plating options
- Package details
- · Application notes
- · Application and design sample kits
- · Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110

Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (000)



Product End of Life Notification

PDN ID:	PDN01024 Rev:001
Notification Date:	10/07/16
Last Buy Date:	11/11/16
Last Shipment Date	5/11/17

Summary: The following high voltage NPN and PNP enchanced specification transistors were discontinued on May 11, 2016, and are currently classified as End of Life (EOL). Rev:001 of PDN#01024, October 7, 2016, is being issued to remove part #s CZT5551E BK and CZT5551E TR from the PDN to address market demand. CZT5551E BK and CZT5551E TR are now active devices.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement	
CMPT5401E BK	CMPT5401 BK	
CMPT5401E TR	CMPT5401 TR	
CMPT5551E BK	CMPT5551 BK	Н
CMPT5551E TR	CMPT5551 TR	Н
CMUT5401E BK	CMUT5401 BK	
CMUT5401E TR	CMUT5401 TR	
CMUT5551E BK	CMUT5551 BK	
CMUT5551E TR	CMUT5551 TR	
CXT5401E BK	CXT5401 BK	H
CXT5401E TR	CXT5401 TR	Н
CXT5551E BK	CXT5551 BK	
CXT5551E TR	CXT5551 TR	
CZT5401E BK	CZT5401 BK	Н
CZT5401E TR	CZT5401 TR	H

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002