



Article Number: 170-03114

Description: Plenum Rated Expandable Braided Sleeving (Halar), 2.0"

Dia, Black, 50 ft/reel

Base Data		
	Local Order Number	170-03114
	Туре	BSHLR200
	Color	Black (BK)
	Features and Benefits	<ul> <li>Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li> <li>Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul>
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia, Black, 50 ft/reel
Product Dimensions		
	Length L (Imperial)	50.0ft
	Length L (Metric)	15.2m
	Reel Length (imperial)	50.0ft
	Bundle Diameter Min. (Imperial)	1.5"
	Bundle Diameter Min. (Metric)	38.1mm
	Bundle Diameter Max. (Imperial)	3.5"
	Bundle Diameter Max. (Metric)	88.9mm
	Diameter D (imperial)	2.0"
	Nominal Diameter (Imperial)	2"
	Nominal Diameter (Metric)	50.8mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE

generated on: 4/28/2017

## 170-03114



ammability	UL VW-1
perating Temperature	-103°F to +302°F (-75°C to +150°C)
OHS Compliant	Yes
ertification/Specification	UL2024
L Recognized (US and Canada)	Yes
ackage Quantity (Imperial)	50ft
ackage Quantity (Metric)	15.24m
ustoms Number(Schedule B)	3926909987
eight (imperial)	2.3lbs
eight (Metric)	1.04kg
r C L	perating Temperature  OHS Compliant  OHS Compliant

generated on: 4/28/2017