

111-03027

Article Number: 111-03027

Description: High-Temp. Cable Tie, 5.8" Long, 30lb Tensile Strength, PA46, Brown, 1000/plain pkg



Base Data	Local Order Number	T30R1STNLM5
	Type	T30R
	Color	Brown (BN)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Cable ties made of PA46 material provide a greater resistance to high heat exposures than PA66 heat stabilized material.</li> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	High-Temp. Cable Tie, 5.8" Long, 30lb Tensile Strength, PA46, Brown, 1000/plain pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		135.0N
Length L (Imperial)		5.8"
Length L (Metric)		148.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.14"
Width W (Metric)		3.6mm
Bundle Diameter Min. (Imperial)		0.06"
Bundle Diameter Min. (Metric)		1.5mm

111-03027

**HellermannTyton**

Product Dimensions	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Thickness T (Metric)	1.1mm
Material and Specifications		
	Material	Polyamide 4.6 (PA46)
	Material Shortcut	PA46
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +275°F (-40°C to +135°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987