

190-00229



Article Number: 190-00229

Description: Snapper Hose Clamp, 3.13"–3.48" Bundle Diameter, PA66GF13, Black, 100/pkg

|                                 |                       |  |
|---------------------------------|-----------------------|--|
| Base Data                       | Local Order Number    | SNP80GHS0C2  |
|                                 | Type                  | SNP80  |
|                                 | Color                 | Black (BK)   |
|                                 | Features and benefits | <ul style="list-style-type: none"> <li>• Designed for quick, ratcheted installation and can be released and reused.</li> <li>• Heat stabilized material is suitable for high temperature applications.</li> </ul>  |
|                                 | Quantity Per          | bag  |
|                                 | Product Description   | HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes. |
|                                 | Short Description     | Snapper Hose Clamp, 3.13"–3.48" Bundle Diameter, PA66GF13, Black, 100/pkg  |
|                                 | Product Dimensions    | Fixation Method  |
| Variant                         |                       | Closed   |
| Width W2 (Imperial)             |                       | 0.332"   |
| Width W2 (Metric)               |                       | 8.43mm   |
| Bundle Diameter Min. (Imperial) |                       | 3.27"  |
| Bundle Diameter Min. (Metric)   |                       | 83.0mm   |
| Bundle Diameter Max. (Imperial) |                       | 3.6"   |
| Bundle Diameter Max. (Metric)   |                       | 92mm   |
| Diameter Min. (Imperial)        |                       | 3.126"   |
| Diameter Min. (Metric)          |                       | 79.4mm   |
| Diameter Max. (Imperial)        |                       | 3.477"   |
| Diameter Max. (Metric)          |                       | 88.32mm  |
| Wall Thickness WT (Imperial)    |                       | .1"  |
| Wall Thickness WT (Metric)      |                       | 2.525mm  |

190-00229



|                             |                             |  |
|-----------------------------|-----------------------------|--|
| Material and Specifications |                             |  |
|                             | Material                    | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%) |
|                             | Material Shortcut           | PA66GF13   |
|                             | Flammability                | UL 94 HB   |
|                             | Operating Temperature       | -40°F to +221°F (-40°C to +105°C)                                      |
|                             | ROHS Compliant              | Yes  |
| Logistic and Packaging      |                             |  |
|                             | Package Quantity (Imperial) | 100  |
|                             | Package Quantity (Metric)   | 100  |
|                             | Customs Number(Schedule B)  | 3926909987   |