



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: UPSRMR11

Supports UPS systems in 4-post rackmount applications

Highlights

- Supports UPS systems in 4-post rackmount applications.
- Supports any rackmount chassis up to 250 lbs
- Includes 2 pairs of expandable "L bracket" mounting rails



Description

Tripp Lite's UPSRMR11 adjustable rackmount shelf system supports heavy UPS systems in 4 post rackmount applications. Two included pairs of expandable "L bracket" mounting rails offer front to rear support of any rackmount chassis up to 250 lbs. Supports UPS systems in 4 post rackmount applications. Pair of expandable "L brackets" adjust to any setting between 23.5 and 36.5 inches. Adding a 2nd UPSRMR11 enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 49.5 inches. Also compatible with other heavy pieces of networking or power protection equipment with 17.5 inch wide rectangular chassis.

Applications

- Ideal for supporting heavy networking and power protection equipment

Package Includes

- UPSRMR11 adjustable rackmount shelf kit
- Owner's manual

Features

- Supports UPS systems in 4 post rackmount applications
- Includes 2 pairs of expandable "L bracket" mounting rails offer front to rear support of any rackmount chassis up to 250 lbs.
- "L brackets" adjust to any setting between 23.5 and 36.5 inches
- A 2nd UPSRMR11 enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 49.5 inches
- Compatible with other heavy pieces of networking or power protection equipment with 17.5 inch wide rectangular chassis

Specifications

PHYSICAL	
Shipping weight (lbs)	5
Shipping weight (kg)	2.3

Unit Dimensions (HWD/in)	6.4 x 61.6 x 6
Material of construction	Steel
Form factors supported	Supports UPS systems in 4 post rackmount applications. Pair of expandable L brackets adjust to any setting between 23.5 and 36.5 inches. Adding a 2nd UPSRMRII enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 4
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2630.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.