

PCB terminal block - FKDSPA1-7,62 - 1789058

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Pitch: 7.62 mm, Number of positions: 1, Connection method: Spring-cage connection, Mounting: Soldering, Color: green

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 144425
Weight per Piece (excluding packing)	5.02 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Length	34 mm
Pitch	7.62 mm
Pin dimensions	0,8 x 1 mm
Hole diameter	1.3 mm

General

Range of articles	FKDSP(A)
Nominal cross section	1.5 mm ²
Solder pin surface	Sn
Inflammability class according to UL 94	V2
Number of positions	1

Classifications

eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101

PCB terminal block - FKDSPA1-7,62 - 1789058

Classifications

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals


Approvals submitted

Approval details

UL Recognized 	
mm ² /AWG/kcmil	12
Nominal current I _N	10 A
Nominal voltage U _N	300 V

PCB terminal block - FKDSPA1-7,62 - 1789058

Approvals

cUL Recognized 	
mm ² /AWG/kcmil	12
Nominal current I _N	10 A
Nominal voltage U _N	300 V

GOST 	
--	--

cULus Recognized 	
--	--