

156-00156

Article Number: 156-00156

Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg



Base Data	Local Order Number	156-00156
	Type	T50SFT6
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
	Quantity Per	bag
	Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
	Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		6.0"
Length L (Metric)		160.0mm
Length L2 (Imperial)		0.46"
Length L3 (imperial)		0.54"
Length L3 (metric)		13.8mm
Fixation Method		Fir Tree
Identification Plate Position		none
Length L2 (Metric)		11.6mm
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"

156-00156



Product Dimensions	Width W (Metric)	4.6mm
	Width W2 (Imperial)	0.35"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.3"
	Height H2 (Metric)	7.5mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	3.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm	
Mounting Hole Diameter D Min. (Imperial)	0.252"	
Mounting Hole Diameter D Max. (Imperial)	0.28"	
Thickness T (Metric)	1.2mm	
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500

156-00156



Logistic and Packaging	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987