

115-00600



Article Number: 115-00600

Description: Releasable Cable Tie, Release Lever, 9.8" Long, 50lb Tensile Strength, PA66, Black, 100/pkg

| Base Data | |
|-------------------------------------|---|
| Local Order Number | REL50L0C2 |
| Type | REL50L |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none"> • Special design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength even after repeated use, ensuring extended longevity. |
| Quantity Per | bag |
| Product Description | HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Releasable Cable Tie, Release Lever, 9.8" Long, 50lb Tensile Strength, PA66, Black, 100/pkg |
| Product Dimensions | |
| Minimum Tensile Strength (Imperial) | 50.0lbs |
| Minimum Tensile Strength (Metric) | 225.0N |
| Length L (Imperial) | 9.8" |
| Length L (Metric) | 250mm |
| Fixation Method | None |
| Identification Plate Position | none |
| Releasable Closure | Yes |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.3" |
| Width W (Metric) | 7.4mm |
| Cable Tie Width Max. (Imperial) | 0.42" |
| Cable Tie Width Max. (Metric) | 10.7mm |
| Height H2 (Imperial) | 0.31" |

115-00600

HellermannTyton

| | | |
|-----------------------------|---------------------------------|----------------------------------|
| Product Dimensions | Height H2 (Metric) | 7.8mm |
| | Bundle Diameter Min. (Imperial) | 0.1" |
| | Bundle Diameter Min. (Metric) | 2.5mm |
| | Bundle Diameter Max. (Imperial) | 2.8" |
| | Bundle Diameter Max. (Metric) | 70.0mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | Flammability | UL 94 V2 |
| | Minimum Application Temperature | - |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 100 |
| | Package Quantity (Metric) | 100 |
| | Customs Number(Schedule B) | 3926909987 |