THIS IS ISSUED IN STRICT CONFIDENCE THAT IT IS NOT USED AS A BASIS FOR MANUFACTURE OR SALE AND THAT IT IS NOT COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE PRIOR WRITTEN CONSENT OF CAL TEST ELECTRONICS, INC.

REVISIONS

REV. DESCRIPTIONS DATE APPROVED

- CLASS A RELEASED 10/24/02

- 1. BNC MALE TO BNC MALE CABLE ASSEMBLY ON RG58C/U COAXIAL CABLE, 50Ω w/MOLDED BEND RELIEF BOOTS.
- 2. SPECIFICATIONS:

CONNECTOR:

BNC MALE CRIMP, 50Ω IMPEDANCE PER MIL-C-39012.

BODY: BRASS OR DIECAST ZINC.

DIELECTRIC: TEFLON.

CENTER PIN: BRASS, GOLD PLATED.

CABLE:

RG58C/U PER MIL-C-17 50Ω, BLACK, Ø0.195 DIAMETER.

MOLDED BOOT MATERIAL:

PVC, BLACK. (MOLDED TO CABLE AND CONNECTOR).

3. RATING:

VOLTAGE: 500Vrms. IMPEDANCE: 50Ω.

TEMPERATURE: 0° C TO +80° C.

PART NUMBER

CT2942-L

LENGTH: (CENTIMETERS)

STANDARDS: 25, 50, 100, 120, 150, 200,

250

THIRD ANGLE PROJECTION		UNLESSOTHERWISESPECIFIED DIMENSIONS ARE IN INCHES	CONTRACT NO.		Cal Test Electronics 22820 Savi Ranch Parkway					
		TOLERANCES ARE: FRACTIONS DECIMALS			Yorba Linda, CA 92887-4604					
			APPROVALS	DATE	TITLE					
			DRAWN WDH	10/20/02] (CABLE ASSEMBLY, BNC MALE TO MALE,				
		MATERIAL	CHECKED		1	RG58C/U, 50Ω				
		FINISH	ENGR.		SIZE	CAGE CODE	DWG. NO.	294200	REV.	
NEXT ASSY	USED ON		DESIGN ACTIVITY		<u> </u>		P294200		_	
APPLICATION		1	,		SCALE	NONE		SHEET 1 OF	2	

