

111-15519



Article Number: 111-15519

Description: Heavy-Duty Cable Tie, 43.1" Long, 175lb Tensile Strength, PA66, Natural, 25/pkg

Base Data	Local Order Number	T150XL9X2
	Type	T150XL
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Heavy-duty design to offer higher tensile strength.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton heavy-duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 43.1" Long, 175lb Tensile Strength, PA66, Natural, 25/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		780.0N
Length L (Imperial)		43.1"
Length L (Metric)		1095.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.35"
Width W (Metric)		8.9mm
Bundle Diameter Min. (Imperial)		6.0"
Bundle Diameter Min. (Metric)		152.0mm
Bundle Diameter Max. (Imperial)		13.0"
Bundle Diameter Max. (Metric)		330.0mm

111-15519



Product Dimensions	Thickness T (Imperial)	0.083"
	Thickness T (Metric)	2.1mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL   ANSI/UL 1565
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	20.8kg