HellermannTyton

Article Number: 181-00027



Description: Slotted Cable and Wiring Duct, 1.5" x 1.5", Adhesive, PVC, Black, 120ft /carton

Base Data		
	Local Order Number	181-00027
	Туре	SLA1.5X1.5
	Color	Black (BK)
	Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1.5" x 1.5", Adhesive, PVC, Black, 120ft /carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.2"
	Width W5 (metric)	30.5mm

181-00027

HellermannTyton

Product Dimensions Height H (Imperial) 1.57" Height H (Metric) 39.9mm Material and Specifications Material (Imperial) 4.0" Material and Specifications Material Polyvinylchloride (PVC) Material Polyvinylchloride (PVC) Material Shortcut PVC Fammability self-extinguishing Operating Temperature +122"F (+50°C) ROHS Compliant Ves Certification/Specification UL UL Recognized (US) Yes Package Quantity (Imperial) 20f Package Quantity (Imperial) 120ft Package Quantity (Metric) 86.6m YestomsUndertification 392590000			
Height H (Metric) 39.9mm Mounting Hole Centers (Imperial) 4.0° Material and Specifications Material And Specifications Material Shortcut Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yees UL Recognized (US) Yees Logistic and Package Quantity (Imperial) 120ft Package Quantity (Imperial) 20ft Package Quantity (Metric) 36.6m Image: Package Quantity (Metric) Image: Package Quantity (Metric) Image: Package Quantity (Metric) Image: Package Quantity (Metric) 		Height H (Imperial)	1.57"
Material and Specifications Material Polyvinylchloride (PVC) Material Polyvinylchloride (PVC) Material Shortcut PVC Flarmability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Ves Certification/Specification UL UL Recognized (US) Yes Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Height H (Metric)	39.9mm
Specifications Adterial Polyvinylchloride (PVC) Material Shortcut PVC Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Mounting Hole Centers (Imperial)	4.0"
Material ShortcutPVCFlammabilityself-extinguishingOperating Temperature+122°F (+50°C)ROHS CompliantYesCertification/SpecificationULUL Recognized (US)YesPackage Quantity (Imperial)120ftPackage Quantity (Metric)36.6m			
Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Material Shortcut	PVC
ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Packaging Ves Package Quantity (Imperial) Yes Package Quantity (Metric) 120ft Section 36.6m		Flammability	self-extinguishing
Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Operating Temperature	+122°F (+50°C)
Image: Non-Stress Packaging Yes Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		ROHS Compliant	Yes
Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Certification/Specification	UL
Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		UL Recognized (US)	Yes
Package Quantity (Metric) 36.6m	Logistic and Packaging		
		Package Quantity (Imperial)	120ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	36.6m
		Customs Number(Schedule B)	3925900000