



Article Number: 184-12007

Slotted Cable and Wiring Duct, High-Density, 1" x 2", Non-Adhesive, PVC, White, 120 ft/carton Description:

Base Data		
	Local Order Number	184-12007
	Туре	SLHD1X2
	Color	White (WH)
	Features and Benefits	<ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li> <li>Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li> <li>Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.</li> </ul>
	Quantity Per	carton
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, High-Density, 1" x 2", Non-Adhesive, PVC, White, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	1.62"
	Width W5 (metric)	41.1mm

generated on: 4/28/2017

## 184-12007



Product Dimensions         Height H (Metric)         52.6mm           Material and Specifications Facility         Material Polyvinylchloride (PVC)           Material Shortcut         PVC           Flammability         self-extinguishing           Operating Temperature         +122°F (+50°C)           ROHS Compliant         Yes           Logistic and Packaging         UL Recognized (US)         Yes           Logistic and Packaging Package Quantity (Imperial)         120ft           Package Quantity (Metric)         36.6m           Customs Number (Schedule B)         3925900000			
Height H (Metric)   52.6mm     Mounting Hole Centers (Imperial)   2.0"     Material and Specifications   Material Shortcut   PVC     Material Shortcut   PVC     Flammability   Self-extinguishing     Operating Temperature   +122°F (+50°C)     ROHS Compliant   Yes     Certification/Specification   CSA     UL Recognized (US)   Yes     Logistic and Packaging     Package Quantity (Imperial)   120ft     Package Quantity (Metric)   36.6m		Height H (Imperial)	2.07"
Material and Specifications Polyvinylchloride (PVC)  Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Height H (Metric)	52.6mm
Specifications  Material  Material  Material Shortcut  Flammability  Operating Temperature  ROHS Compliant  Certification/Specification  UL Recognized (US)  Package Quantity (Imperial)  Package Quantity (Metric)  Polyvinylchloride (PVC)  PVC  PVC  Flammability  self-extinguishing  +122°F (+50°C)  CSA  CSA  UL Recognized (US)  Yes  Package Quantity (Imperial)  120ft  Package Quantity (Metric)  36.6m		Mounting Hole Centers (Imperial)	2.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m			
Flammability  Operating Temperature  +122°F (+50°C)  ROHS Compliant  Yes  Certification/Specification  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  Self-extinguishing  +122°F (+50°C)  Yes  CSA  USA  UL Recognized (US)  Yes  120ft  Package Quantity (Metric)  36.6m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification CSA  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 120ft  Package Quantity (Metric) 36.6m		Material Shortcut	PVC
ROHS Compliant  Certification/Specification  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  Package Quantity (Metric)  Yes  Logistic and Package Quantity (Imperial)  120ft  Package Quantity (Metric)  36.6m		Flammability	self-extinguishing
Certification/Specification UL Recognized (US)  Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  CSA  Yes  Logistic and Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Operating Temperature	+122°F (+50°C)
Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  Package Quantity (Metric)  Yes  120ft Package Quantity (Metric)  36.6m		ROHS Compliant	Yes
Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  120ft Package Quantity (Metric)  36.6m		Certification/Specification	CSA
Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  120ft  Package Quantity (Metric)  36.6m		UL Recognized (US)	Yes
Package Quantity (Metric) 36.6m			
		Package Quantity (Imperial)	120ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	36.6m
		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017