

Panel feed-through - Q 1,5/2FL/13-13KU-ESA - 1670264

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



QUICKON panel feed-through, for external wall mounting with manual solder/slip-on connection, 4.8 x 0.8 mm, 3-pos.



Key commercial data

| | |
|------------------------|---------------------|
| Packing unit | 1 |
| Minimum order quantity | 100 |
| Catalog page | Page 18 (PC-2002) |
| GTIN | 4 017918 146474 |
| Custom tariff number | 85369010 |
| Country of origin | POLAND |

Technical data

General characteristics

| | |
|--|---|
| Connection | If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load. |
| Color | green |
| Connection method | Manual solder/slip on connection |
| Number of positions | 3 |
| Wrench size, union nut | 24 mm |
| Tightening torque, union nut | 2.5 Nm |
| Wrench size, contact carrier | 24 mm |
| Tightening torque contact carrier | 3.75 Nm |
| Tightening torque, counter nut | 3.75 Nm |
| Number of connections | 3 |
| Conductor cross section stranded min. | 0.75 mm ² |
| Conductor cross section stranded max. | 1.5 mm ² |
| Conductor cross section AWG/kcmil min. | 18 |
| Conductor cross section AWG/kcmil max | 16 |

Conductor data

Panel feed-through - Q 1,5/2FL/13-13KU-ESA - 1670264

Technical data

Conductor data

| | |
|---|--|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 Cl.2-5, min. wire diameter 0.2 mm |
| Wire insulation material | PVC/PE |
| Wire diameter including insulation | >= 3 mm |

Environmental conditions

| | |
|---------------------------------|---|
| Degree of protection | IP65/67 |
| Ambient temperature (operation) | -25 °C ... 80 °C |
| Ambient temperature (operation) | -25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.) |

Electrical characteristics

| | |
|-----------------------------------|--|
| Nominal current I _N | 17.5 A (15 A with slip-on sleeve 2.5 mm ² ; 12 A with slip-on sleeve 1.5 mm ² .) |
| Rated voltage (III/3) | 250 V |
| Note on the rated voltage (III/3) | with insulating sleeve |
| Rated voltage (III/2) | 320 V |
| Note on the rated voltage (III/2) | with insulating sleeve |
| Rated voltage (II/2) | 630 V |
| Note on the rated voltage (II/2) | with insulating sleeve |

Mechanical characteristics

| | |
|------------------------|--|
| QUICKON connectability | 10 (if the conductor is connected more than once, seal and cap may need to be replaced.) |
| PC QUICKON thread type | Pg13.5 VDE certification available |
| Impact category | 4 |

Material data

| | |
|---|----------------------------------|
| Contact material | Copper alloy |
| Contact surface material | Pre-nickel plated and tin-plated |
| Contact carrier material | PA 66 |
| Inflammability class according to UL 94 | V0 |
| Surge voltage category | III |
| Pollution degree | 3 |

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001297 |
| ETIM 3.0 | EC000516 |
| ETIM 4.0 | EC000516 |
| ETIM 5.0 | EC000516 |

UNSPSC

| | |
|--------------|----------|
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |

Panel feed-through - Q 1,5/2FL/13-13KU-ESA - 1670264

Classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 13.2 | 39121522 |
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / GOST / BV / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

| | |
|---|-------|
| UL Recognized  | |
| Nominal current IN | 15 A |
| Nominal voltage UN | 250 V |


| | |
|--|-------|
| cUL Recognized  | |
| Nominal current IN | 11 A |
| Nominal voltage UN | 250 V |

Panel feed-through - Q 1,5/2FL/13-13KU-ESA - 1670264

Approvals



| | |
|--------------------------------|--------|
| BV | |
| mm ² /AWG/kcmil | 1.5 |
| Nominal current I _N | 17.5 A |
| Nominal voltage U _N | 250 V |



Accessories

Accessories

Assembly

Lock nut - Q-SMU PG13,5 SET COD2 - 1670963



Locking nut, can only be released with Allen wrench, coding 2

Nut - Q-MU PG13,5 - 1670484



Nut (plastic) to lock the contact carrier Pg13.5 / 27 WAF

Insulating sleeve - PT/FS 4,8 - 1670497



Insulating sleeve, as touch protection, for 4.8 mm slip-on sleeves, slide onto the conductor before

Protection and sealing elements

Panel feed-through - Q 1,5/2FL/13-13KU-ESA - 1670264

Accessories

Cover caps - Q-PROT13/16 - 1670222



Closing caps, for Pg13/ Pg16, for closing unoccupied connections

Tools

Socket wrench - QSS 24 - 1670219



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 24 mm

Drawings

Dimensioned drawing

