

156-00054

Article Number: 156-00054

Description: Fir Tree Mount and Cable Tie, 50 lbs, 12.0" Long, Fixing Hole Dia .26"-.28", PA66HS, Black, 500/pkg



Base Data	
Local Order Number	156-00054
Type	T50IFT6LG
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
Short Description	Fir Tree Mount and Cable Tie, 50 lbs, 12.0" Long, Fixing Hole Dia .26"-.28", PA66HS, Black, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225N
Length L (Imperial)	12.0"
Length L (Metric)	305.0mm
Length L2 (Imperial)	0.43"
Length L3 (imperial)	0.69"
Length L3 (metric)	17.5mm
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	11.6mm
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18"

156-00054



Product Dimensions	Width W (Metric)	4.6mm
	Width W2 (Imperial)	0.35"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.44"
	Height H2 (Metric)	11.1mm
	Bundle Diameter Max. (Imperial)	3.3"
	Bundle Diameter Max. (Metric)	85.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.24"
	Panel Thickness Max. (Metric)	6.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.256"
Mounting Hole Diameter D Max. (Imperial)	0.276"	
Thickness T (Metric)	1.2mm	
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987