








APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	 -55 °C TO +85 °C	STORAGE TEMPERATURE RANGE	  -55 °C TO +85 °C	
	VOLTAGE		CURRENT		
<b>SPECIFICATIONS</b>					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
<b>CONSTRUCTION</b>					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
 3	DIS-E-002200	MT. ITANO	HK. TANAKA	08.03.11	
REMARK		APPROVED	HO. MIWA	05.01.05	
  PACKING MATERIAL IS NOT INCLUDED.		CHECKED	TH. KAMEYA	05.01.05	
		DESIGNED	SS. SATOH	05.01.05	
Unless otherwise specified, refer to JIS C 5402.		DRAWN	SS. SATOH	05.01.05	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-121484-03		
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	TM21P-88P (22)		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2862-9-22		1/1