

111-12036

Article Number: 111-12036

Description: Heavy-Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Natural, 500/pkg



Base Data	Local Order Number	T120R9H4
	Type	T120R
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> • Heavy duty design to offer higher tensile strength. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Natural, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		535.0N
Length L (Imperial)		15.2"
Length L (Metric)		387.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.3"
Width W (Metric)		7.6mm
Bundle Diameter Min. (Imperial)		0.2"
Bundle Diameter Min. (Metric)		5.0mm
Bundle Diameter Max. (Imperial)		4.1"

111-12036



Product Dimensions	Bundle Diameter Max. (Metric)	105.0mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3367-3-9
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	DNV GL
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987