

131-75019

Article Number: 131-75019

Description: Releasable Cable Tie, Release Tab, 20.3" Long, 250lb Tensile Strength, PA66, Natural, 25/pkg



|                                   |                       |   |
|-----------------------------------|-----------------------|---|
| Base Data                         | Local Order Number    | RT250R9X2   |
|                                   | Type                  | RT250R  |
|                                   | Color                 | Natural (NA)  |
|                                   | Features and Benefits | <ul style="list-style-type: none"> <li>• Special extended-pawl design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>• Buckle feature on head allows excess strap to be tucked away after installation.</li> </ul>       |
|                                   | Quantity Per          | bag   |
|                                   | Product Description   | HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
|                                   | Short Description     | Releasable Cable Tie, Release Tab, 20.3" Long, 250lb Tensile Strength, PA66, Natural, 25/pkg  |
|                                   | Product Dimensions    | Minimum Tensile Strength (Imperial)   |
| Minimum Tensile Strength (Metric) |                       | 1115.0N   |
| Length L (Imperial)               |                       | 20.3"   |
| Length L (Metric)                 |                       | 515.0mm   |
| Fixation Method                   |                       | None  |
| Identification Plate Position     |                       | none  |
| Releasable Closure                |                       | Yes   |
| Tie Closure                       |                       | plastic pawl  |
| Variant                           |                       | Inside Serrated   |
| Width W (Imperial)                |                       | 0.49"   |
| Width W (Metric)                  |                       | 12.5mm  |
| Bundle Diameter Min. (Imperial)   |                       | 0.47"   |
| Bundle Diameter Min. (Metric)     |                       | 12.0mm  |

131-75019



|                               |                                  |                                  |
|-------------------------------|----------------------------------|----------------------------------|
| Product Dimensions            | Bundle Diameter Max. (Imperial)  | 4.9"                             |
|                               | Bundle Diameter Max. (Metric)    | 125.0mm                          |
|                               | Thickness T (Imperial)           | 0.075"                           |
|                               | Cable Tie Head Length (Imperial) | 0.88"                            |
|                               | Cable Tie Head Width (Imperial)  | 0.79"                            |
|                               | Thickness T (Metric)             | 1.9mm                            |
| Material and Specifications   |                                  |                                  |
|                               | Material                         | Polyamide 6.6 (PA66)             |
|                               | Material Shortcut                | PA66                             |
|                               | Flammability                     | UL 94 V2                         |
|                               | Minimum Application Temperature  | -                                |
|                               | Operating Temperature            | -40°F to +185°F (-40°C to +85°C) |
|                               | REACH Compliant (Article 33)     | Yes                              |
|                               | ROHS Compliant                   | Yes                              |
|                               | Certification/Specification      | DNV GL                           |
| UL Recognized (US and Canada) | Yes                              |                                  |
| Logistic and Packaging        |                                  |                                  |
|                               | Package Quantity (Imperial)      | 25                               |
|                               | Package Quantity (Metric)        | 25Pieces                         |
|                               | Customs Number(Schedule B)       | 3926909987                       |
|                               | Content Unit (BMEcat)            | pieces                           |
|                               | Weight (Metric)                  | 12.2kg                           |