

**RIDERSERIES
RCH S51024****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



- Relay with positively driven contacts acc. to EN 50205
- 2 CO contacts or 1 NOC + 1 NCC
- 1500 VA switching capacity
- 6 kV impulse withstand voltage

General ordering data

Order No.	8768700000
Type	RCH S5 1024
Version	RIDERSERIES, No. of contacts: 1, NC and NO contact, AgNi, Rated control voltage: 24 V DC, Continuous current: 6 A, Screw connection
GTIN (EAN)	4032248437481
Qty.	20 pc(s).

RIDERSERIES
RCH S51024

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Ratings

Conductor connection system	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Weight	20 g		

Dimensions and weights

Length	29 mm	Width	12.6 mm
Height	25.5 mm	Weight	20 g
Net weight	19.2 g		

Temperatures

Operating temperature	-25 °C...+70 °C	Storage temperature	
-----------------------	-----------------	---------------------	--

Input

Rated control voltage	24 V DC	Rated current DC	29.2 mA
Power rating	700 mW	Pull-in (sparkover) / drop-out voltage DC coil	18.0 V / 2.4 V
Status indicator	No		

Output

Max. switching voltage, AC	250 V	Continuous current	6 A
Max. switching power	1500 VA	Response time	10 ms / 4 ms

Contact specifications

No. of contacts	1	Contact design	NC and NO contact
Contact material	AgNi	Mechanical service life	10 x 10 ⁶ switching cycles

Insulation coordination

Clearance and creepage distances for control side - load side	> 8 mm	Creepage and clearance distances between contacts	5.5 mm
Pollution severity	2	Surge voltage category	III

Other technical data

Status indicator	No	Free-wheel diode	No
------------------	----	------------------	----

Further details of approvals / standards

Standards	IEC 61810-1, UL508
-----------	--------------------

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	39-12-15-35
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

Data sheet...

**RIDERSERIES
RCH S51024**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals




**RIDERSERIES
RCH S51024**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Electric symbol**

Circuit diagram
View of connections

2 changeover contacts



1 NOC + 1 NCC

