Description	Material	Finish		REVISIONS						
Body	Brass	Gold			REV		DESCRIPTION		DATE	APPV
Socket	BE CU	Gold			B A	Added new title block	{	1.	1-JUL-12	SAH
Insulation	PTFE	N/A					-			
Washer	Brass	Gold								
Nut	Brass	Gold								
Ø0.051 (1.30)	0.024 (0.60) 0.106 (2.70)	SIDE \ 10-56U THRI FLAT 0.17 (4.40) 0.256 (6.50) 0.386 (9.80)	INS-2A EADS	00.250 6.35) 024 60)	BACK VIEW		NUT	- +0.250 (6.35) Ø0.377 (9.57)	VASHER	
RECOMMENDED MOUNTING HOLE			INTING	NOTES: (UNLESS OTHERWISE SPECIFIED) 1. ALL DIMENSIONS ARE IN INCHES [mm]. 2. DIMENSIONS APPLY AFTER FINISHING. 3. MANUFACTURE TO BE COMPLIANT WITH EU RoHS DIRECTIVE. 4. SAFETY BREAK ALL SHARP CORNERS AND EDGES .02 MAXIMUM.						
			AT 0.173 (4.40)	DOCUMENT IS PERMIT EXPRESS WRITTEN P	ERTY OF LINX TECHNOL D DISCLOSURE OR REPRITED, IN WHOLE OR IN P ERMISSION OF LINX TEC DESIGNATED AGENTS. TOLERANCES: .020 [0.50]-1200 [30.00]= ±.1	ETARY INFORMATION OGIES, AND SHALL BE ODUCTION OF THIS ART, WITHOUT THE CHNOLOGIES OR ITS			ORT LAN I, OR 97 HEAD	IE '532
	 Ø0. (4.⁻ 			FINISH:	1.20 [30.0]-4.75 [120.0]= ± 4.75 [120.0]-12.40 [315.0] DRAWN: B.MURP	+ <u>+ .040 [1.0]</u> ANGLES: <u>+</u> 1 PHY DT: 11-JUL-12	A	CONMCX	004	B