

111-04300

Article Number: 111-04300

Description: Standard Cable Tie, 14.6" Long, 40lb Tensile Strength, PA66, Natural, 100/pkg



Base Data	
Local Order Number	T40L9C2
Type	T40L
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Standard Cable Tie, 14.6" Long, 40lb Tensile Strength, PA66, Natural, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	180.0N
Length L (Imperial)	14.6"
Length L (Metric)	370.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.16"
Width W (Metric)	4.0mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm
Bundle Diameter Max. (Imperial)	4.13"
Bundle Diameter Max. (Metric)	105.0mm

111-04300



Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-ZODZ2.E64139
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987