

170-03099



Article Number: 170-03099

Description: Plenum Rated Expandable Braided Sleeving (Halar), 0.12" Dia, White, 225 ft/reel

Base Data	Local Order Number	170-03099
	Type	BSHLR1810
	Color	White (WH)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>• Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li> <li>• Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul>
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 0.12" Dia, White, 225 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		68.6m
Reel Length (imperial)		225.0ft
Width W (Imperial)		0.01"
Width W (Metric)		.25mm
Bundle Diameter Min. (Imperial)		0.094"
Bundle Diameter Min. (Metric)		2.4mm
Bundle Diameter Max. (Imperial)		0.25"
Bundle Diameter Max. (Metric)		6.4mm
Nominal Diameter (Imperial)		1/8"
Nominal Diameter (Metric)		3.1mm
Material and Specifications	Material	Polyamide 6.6 (PA66E/CTFE)

170-03099



Material and Specifications	Material Shortcut	PA66E/CTFE
	Flammability	FAR 25
	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	225ft
	Package Quantity (Metric)	68.58m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.56lbs