



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Protect It! 6-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Ethernet Protection, Safety Covers

MODEL NUMBER: TLP66NET



### Highlights

- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet surge protection
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- TLP66NET
- 6-ft. network cable
- Instruction manual with warranty information

### Description

Tripp Lite's TLP66NET surge suppressor has 6 outlets, a 6-ft. cord and diagnostic LEDs. The unit has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6-ft network cable included). \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications

| OUTPUT                  |           |
|-------------------------|-----------|
| Frequency Compatibility | 60 Hz     |
| Output Receptacles      | (6) 5-15R |
| Output (Watts)          | 1800      |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                           |  |
|---------------------------|--|
| Circuit Breaker (amps)    | 15   |
| Overload Protection       | 15A resettable illuminated combo switch / circuit breaker  |
| Transformer Accommodation | Supports 2 large transformer plug accessories without covering remaining outlets, accepts up to 4 transformers total |
| Outlet Safety Covers      | 6  |
| Outlet Orientation        | Block style with two rows of 3 outlets   |
| Right-Angle Outlets       | No   |

#### INPUT

|                                    |                 |
|------------------------------------|-----------------|
| Nominal Input Voltage(s) Supported | 120V AC         |
| Recommended Electrical Service     | 120V (110-125V) |
| Input Connection Type              | NEMA 5-15P      |
| Input Cord Length (ft.)            | 6               |
| Input Cord Length (m)              | 1.83            |
| Input Cord Gauge Type              | 14 gauge, SJT   |
| Voltage Compatibility (VAC)        | 120             |
| Maximum Surge Amps                 | 72000           |
| Right-Angle Plug                   | No              |

#### USER INTERFACE, ALERTS & CONTROLS

|                        |   |
|------------------------|---|
| Switches               | Combination AC circuit breaker and 2-position red illuminated on/off power switch         |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |

#### SURGE / NOISE SUPPRESSION

|                              |  |
|------------------------------|--|
| AC Suppression Joule Rating  | 1080   |
| AC Suppression Response Time | < 1 ns   |
| Protection Modes             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping Voltage (RMS)       | 150  |
| UL1449 Let Through Rating    | 400v   |
| EMI / RFI Filtering          | Up to 40 dB  |

#### DATALINE SURGE SUPPRESSION

|                               |     |
|-------------------------------|-----|
| Telephone/DSL Protection      | No  |
| Cable (Coax) Protection       | No  |
| Network (Ethernet) Protection | Yes |

#### PHYSICAL



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |  |
|--|--|
| Shipping Dimensions (hwd / in.)                            | 11.02 x 7.08 x 1.77  |
| Shipping Dimensions (hwd / cm)                             | 27.99 x 17.98 x 4.50   |
| Shipping Weight (lbs.)                                     | 1.97   |
| Shipping Weight (kg)                                       | 0.89   |
| Unit Dimensions (hwd / in.)                                | 1.5 x 4.23 x 8.29  |
| Unit Dimensions (hwd / cm)                                 | 3.81 x 10.74 x 21.06   |
| Unit Weight (lbs.)   | 1.32   |
| Unit Weight (kg)   | 0.60   |
| Material of Construction                                   | Plastic  |
| Integrated Keyhole Mounting Tabs                           | Keyhole mounting tabs enable wall mounting   |
| Housing Color  | Light Gray   |
| Receptacle Color   | Dark Gray  |
| Color (AC Line Cord)                                       | Light Gray   |
| Outlets Measurement (Center to Center)                     | Distance between standard outlets = 28.5; Distance between standard outlet and transformer outlet = 48.5mm |
| Keyhole Slot Mounting Measurement (Center to Center)       | 119mm  |
| <b>CERTIFICATIONS</b>                                      |  |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd Edition   |
| UL1363 (Power Tap)   | UL1363   |
| cUL / CSA (Canada)   | cUL  |
| Industry Canada (Communications)                           | Industry Canada  |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |
| <b>WARRANTY</b>  |  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 <a href="#">Ultimate Lifetime Insurance</a>   |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>