
KEMET Part Number: C124K473K5R5CA

(CK13BR473K)



Capacitor, Ceramic, 0.047 uF, +/-10% Tol, 50 V, X7R



General Information		
Supplier:	KEMET	
Application:	General Purpose	
Temperature Coefficient:	X7R	
Body Type:	Axial Molded	
Lead Type:	Wire Leads	
Termination Type:	Tin-Lead (SnPb)	
RoHS:	No	

Dimensions (mm)		
Symbol	Dimension	Tolerance
D	2.29	+/-0.25
L	6.35	+/-0.25
LL	38.1	MIN
F	0.51	-0.08

Specifications		
Capacitance:	0.047 uF	
Voltage:	50 V	
Tolerance:	+/-10%	
Temperature Range:	-55/+125C	
Failure Rate:	N/A	
Dissipation Factor:	2.5%	
Insulation Resistance:	21.3 GOhm	
Dielectric Strength:	125 V	

Notes:

-Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk

Packaging Specifications		
Package Kind:	Bulk	
Package Type:	Bag	
Package Quantity:	200	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

